

ExxonMobil Chemical Isopar M

Written by PT. Chemical Mandiri Jaya

Sunday, 15 May 2011 10:38 - Last Updated Sunday, 15 May 2011 10:51

ExxonMobil Chemical Isopar™ M (AM) Isoparaffin Fluid Isopar™ M (AM)

Isoparaffin Fluid

Product Description

Isopar™ M is clear isoparaffin fluid, typically containing less than 1 ppm benzene and less than 1 ppm

General

Availability 1

- Asia Pacific

- Central America

- North America

- South America

Appearance

- Clear/Transparent

Form(s)

- Liquid

Revision Date

- October 2008

| Properties | Typical Value | Unit | Test Based On |
|-----------------------------|---------------|------|---------------|
| Distillation Range | ASTM D86 | | |
| Initial Boiling Point (IBP) | 225 | °C | |
| Dry Point (DP) | 253 | °C | |

ExxonMobil Chemical Isopar M

Written by PT. Chemical Mandiri Jaya

Sunday, 15 May 2011 10:38 - Last Updated Sunday, 15 May 2011 10:51

| | | | |
|---------------------|------------|--------|--------------------|
| Flash Point | (Method A) | 94 | °C |
| Aromatic Content | (UV) | 40 | wtpm |
| Density | (15.6°C) | 0.785 | g/ml |
| Vapor Pressure | (20.0°C) | < 0.01 | kPa |
| Aniline Point | (Method E) | 93 | °C |
| Kinematic Viscosity | (25.0°C) | 4.23 | mm ² /s |

Additional Information

Typical values listed represent product from a primary source location. Actual values may vary slightly.

Legal Statement

This product, including the product name, shall not be used or tested in any medical application without the approval of the manufacturer.

Notes

¹ Product may not be available in one or more countries in the identified Availability Regions.

For additional technical, sales and order assistance:

Worldwide and the Americas

ExxonMobil Chemical Company

13501 Katy Freeway

Houston, TX 77079-1398

USA

1-281-870-6050

Asia Pacific

ExxonMobil Chemical Singapore Pte. Ltd.

1 HarbourFront Place

#06-00 HarbourFront Tower One

Singapore 098633

66-2163-8444

Europe, Middle East and Africa

ExxonMobil Chemical Europe

Hermeslaan 2

1831 Machelen, Belgium

420-239-016-274

Typical properties: these are not to be construed as specifications.

The values indicated in this document may deviate from the test method requirements by the number of significant figures shown.

© 2011 ExxonMobil. To the extent the user is entitled to disclose and distribute this document, the user may forward, distribute, and/or photocopy this copyrighted document only if unaltered and complete, including all of its headers, footers, disclaimers, and other information. You may not copy this document to a Web site. ExxonMobil does not guarantee the typical (or other) values. Analysis may be performed on representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, suitability, accuracy, reliability, or completeness of this information or the products, materials, or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage, or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. There is no endorsement of any product or process, and we expressly disclaim any contrary implication. The terms, "we", "our", "ExxonMobil Chemical", or "ExxonMobil" are used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates they directly or indirectly steward. ExxonMobil, the ExxonMobil Logo, the Interlocking "X" Device, and all other product names used herein are trademarks of ExxonMobil unless indicated otherwise.

// //]]> // //]]>

&amp;amp;amp;amp;amp;amp;lt;/div&amp;amp;amp;amp;amp;amp;gt;& p&amp;amp;amp;amp;amp;amp;lt;img width="1" src="http://www.sdc.exxonmobil.com/dcsu9ayfy9s9lifelvy0aj9xq_2e4n/njs.gif?dcsuri=/nojavascri pt&amp;amp;amp;amp;amp;amp;WT.js=No&amp;amp;amp;amp;amp; amp;amp;WT.tv=8.6.2" mce_src="http://www.sdc.exxonmobil.com/dcsu9ayfy9s9lifelvy0aj9xq_2e4n/njs.gif?dcsuri=/noja vascript&amp;amp;amp;amp;amp;amp;WT.js=No&amp;amp;amp;amp; amp;amp;amp;WT.tv=8.6.2" id="DCSIMG" height="1" alt="DCSIMG"&amp;amp;amp;amp;amp;gt;&amp;amp;amp;amp; amp;lt;/div&amp;amp;amp;amp;amp;gt;

// // //

ExxonMobil Chemical Isopar M

Written by PT. Chemical Mandiri Jaya

Sunday, 15 May 2011 10:38 - Last Updated Sunday, 15 May 2011 10:51

// //